UJEAS

UNIZIK JOURNAL OF ENGINEERING AND APPLIED SCIENCES

UNIZIK Journal of Engineering and Applied Sciences 6(3), September (2026), 3781-3796
Journal homepage: https://journals.unizik.edu.ng/index.php/ujeas
PRINT ISSN: 2992-4383 || ONLINE ISSN: 2992-4391

Unlocking the Potential: A Detailed Characterization of n-Hexane Extracted Sweet Orange Seed Oil as a Sustainable Industrial Feedstock

Timothy Amaechi Ezidinma*
Chemical Engineering, Institute of Management and Technology, Enugu, Enugu State
Joseph Tagbo Nwabanne
Chemical Engineering, Nnamdi Azikiwe University Awka, Anambra State, Nigeria.
Callistus Nonso Ude
Chemical Engineering, Michael Okpara University of Agriculture, Umudike, Abia State

Corresponding Author's E-mail: timotyezidinma@gmail.com

Abstract
This study conducted an extensive characterization of sweet orange seed oil (SOSO), extracted using the Soxhlet method with n-hexane, to evaluate its potential as a feedstock for industrial applications. The extraction produced 41.64% (w/w) of a light-yellow oil containing 0.249% moisture. The characterization revealed that at 40 °C, the kinematic viscosity was 29.450 mm²/s, the refractive index was 1.437 at 30 °C, and the acid value was 9.24 mgKOH/g, indicating a free fatty acid (FFA) content of 4.67 mgKOH/g. The iodine value was determined to be 107.78 meq/100g, suggesting the oil is highly unsaturated. Further tests showed a saponification value of 243.446 mgKOH/kg, a peroxide value of 0.410 meq/g, a specific gravity of 0.920, and a molecular weight of 1114.68 g/mol. The thermal properties included a flash point of 217 °C, a cloud point of 12.0 °C, and a melting point of 3.5 °C. The ester value was 62.019%. The physicochemical properties closely matched those specified in ASTM D6751f, indicating that SOSO could serve as a non-edible substitute for conventional vegetable oils. Gas Chromatography-Mass Spectrometry (GC-MS) analysis showed that 71.35% of the fatty acids were unsaturated, primarily Oleic (4.34%) and Linoleic acids (67.01%), suggesting excellent cold-flow properties and high reactivity for chemical conversion. Additionally, Fourier Transform Infrared (FTIR) spectroscopy identified characteristic ester functional groups at 1745 cm^{-1}, with the C=O (carbonyl) stretching vibration indicating good structural integrity. This comprehensive study concludes that the oil has favorable properties for long-term use across various industries, particularly in biodiesel and bio-lubricant production.
Keywords: Soxhlet Extraction, sustainable biodiesel, sweet orange, Bio-industrial Feedstock.

1. Introduction

As the world moves towards a circular economy, the need for eco-friendly methods to reuse agro-industrial waste becomes increasingly important. The value of a circular economy is evident. Research shows that the citrus industry is one of the largest producers of organic waste in agriculture (Dubey et al., 2023; Lucia et al., 2022; Maqbool et al., 2023; Mruthunjaya et al., 2025). Globally, citrus fruits are mainly grown for juice, and processing generates millions of tons of waste each year, primarily peels, pulp, and seeds (Dubey et al., 2023; Mruthunjaya et al., 2025; Pratiksha and Adhikary, 2024). In processing regions, especially in southern Nigeria, these leftovers are often discarded in open landfills, harming the environment by releasing greenhouse gases (Maqbool et al., 2023; Dubey et al., 2023). Bioresource engineering research indicates that these wastes, particularly sweet orange (Citrus sinensis) seeds, are not merely garbage but contain high levels of oil with significant industrial potential (Ávila et al., 2025; Prasad, 2024; Warra and Reyna-Patel et al., 2019). Studies indicate that Citrus sinensis seeds are a valuable source of non-edible oils, known as sweet orange seed oils (SOSO), which can serve as a promising alternative raw material for biodiesel and biolubricants. They also help address the important "food vs. fuel" dilemma associated with first-generation feedstocks such as palm or soybean oil (Moreno-Gómez et al., 2020; Pandit et al., 2023). Proper characterization of the oil is essential for evaluating its suitability for applications such as bio-lubricants, alkyd resins, and biodiesel. Soxhlet extraction with n-hexane has proven to be an effective method for extracting seed oil, producing high-quality extracts that preserve the seed's natural chemical composition (AOAC, 2019; Kumar et al., 2025; Mustapha et al., 2024; Ogwuche et al., 2026; Shakya et al., 2025).

Additionally, SOSO is suggested to have a unique fatty acid composition, with high levels of unsaturated fatty acids like oleic and linoleic acids (Al-Okbi et al., 2025; Fadairo et al., 2023; Kamińska et al., 2025), which are important for oxidative stability and flow properties in bio-industrial products such as biodiesel and bio-lubricants (Kudli, 2023; Laverdura et al., 2020). Analytical techniques like Gas Chromatography-Mass Spectrometry (GC-MS) and Fourier Transform Infrared (FTIR) spectroscopy are essential for identifying specific fatty acids and

functional groups (Farag et al., 2025; Nazri, 2025). Developing a detailed fatty acid profile will help create strategies to turn this environmental challenge into valuable industrial resources (Singh et al., 2025; Sirohi et al., 2025; Verma & Dubey, 2024). Comparing these chemical properties, such as iodine value, saponification value, and kinematic viscosity, with international standards, such as ASTM D6751, will help assess its viability (Khalighi, 2024; Nayak et al., 2025; Onyia et al., 2024).

While most studies focus on general citrus seed oils, this research specifically explores the efficiency of n-hexane Soxhlet extraction. It includes detailed analysis using GC-MS and FTIR to determine the structural and lipid makeup of Nigerian varieties. This offers a clear insight into their chemical traits and confirms the composition of sweet orange seed oil from Southern Nigeria's agro-industrial areas. Moreover, this study is among the first to assess the "waste-to-wealth" potential of these local residues under strict standards like ASTM D6751, highlighting their importance in a specialized circular bio-economy.

Despite growing interest in non-edible oils, research on the detailed physicochemical and functional-group makeup of Nigerian sweet orange seed oil (SOSO) remains limited, especially as a sustainable alternative to traditional first-generation feedstocks. Most existing studies focus on the broader citrus family or lack comprehensive instrumental data needed to verify its oxidative stability and flow characteristics for high-value biolubricants and alkyd resins. This study fills that void by presenting a detailed lipid profile that differentiates Nigerian SOSO from Mediterranean or Asian varieties. Consequently, it provides valuable insights into converting an environmental pollutant, which currently adds to greenhouse gas emissions from landfills, into an industrial resource—offering a dual solution for waste management and renewable energy.

2.0 Materials and methods

2.1 Materials and reagents

Orange seeds were collected from the waste bins of fresh fruit vendors at Odegba in New Market, Enugu State, Nigeria. The extracting solvent (n-hexane) and other chemicals used were purchased from Conraws Chemical and Laboratory Equipment Ltd, Enugu, Enugu State, Nigeria. The chemicals were of analytical reagent grade (Sigma-Aldrich) and were used without further purification.

2.2. Sample pre-treatment

The seeds were manually separated from the fruit pulp, washed several times with clean water, and then rinsed repeatedly with distilled water to remove contaminants. The seeds were dried in the sun for six hours each day over five days, then dried in an oven at 110 °C for six hours to ensure a moisture content below 5%. The dried seeds were decorticated, and the kernels were ground into a fine powder using a mechanical grinder. The meal was sifted to achieve a uniform particle size of about 0.5 mm and stored in airtight containers until extraction.

2.3. Oil extraction

Oil was extracted from sweet orange seeds by direct leaching with n-hexane as the solvent, following the AOAC 2003.06 (2006) protocol and the Randall/Soxtec extraction procedure. An isomantle heating mantle on an adjustable platform facilitated easy removal or adjustment, with a three-neck round-bottom flask placed on it. A vertical reflux condenser with water hoses on each arm was fitted securely onto the flask—connected to the water faucet at the lower arm and draining into the sink at the upper arm. The flask vent was sealed to prevent vapor loss, and a thermometer was inserted through a rubber bung fitted tightly into one opening to monitor temperature. Another rubber bung sealed the inlet for adding the solvent and samples. The setup was stabilized with a retort stand, with clamps at the flask's main neck and the condenser. For each sample, 1.5 mL of n-hexane per gram of sample was measured using a measuring cylinder and funnel, then added to the flask. Water was filled into the reflux condenser, which drained into the sink as the heating mantle was turned on. The temperature was maintained at 40 °C and monitored with the thermometer. Once the temperature was stabilized, 2 g of the sample was added to the solvent to initiate oil extraction by leaching. The addition time marked the start, and extraction continued for 50 minutes at 40 °C. Afterward, the heating mantle was turned off, and the apparatus was carefully disassembled. The mixture was filtered under vacuum through a Millipore glass base and funnel, and the resulting solution was poured into a pre-weighed flask. The oil was separated from n-hexane using a rotary vacuum evaporator (Labora 4000), collected in a receiving flask, and weighed and recorded. The oil yield was calculated as per Equation (1).

$$Y = \frac{Wo}{w} \times 100 \quad (1)$$

2.4 Acid Esterification of Sweet Orange Seed Oil

In the transesterification of high FFA (sweet orange seed) oils using a base catalyst, the FFA content must be reduced to below 2 mg KOH/g or 0.1 wt% to prevent soap formation (Ezidinma et al., 2015; Salaheldeen et al., 2021). This was achieved through acid-catalyzed esterification, following a modified method outlined by Ezidinma et al. (2025). The oil sample was dehydrated by heating to 105°C for 20 minutes to remove trace moisture that could interfere with esterification. An acid-methanol mixture was prepared separately by adding a calculated amount of H_2SO_4 (98% assay), corresponding to 1 w/w% of the oil, to the measured alcohol in a 6:1 alcohol-to-oil ratio. This mixture was then added to the oil in a reactor equipped with a reflux condenser. The reaction was maintained at 65°C for 90 minutes with constant stirring at 600 rpm. Afterwards, the mixture was allowed to settle in a separating funnel for 2 hours. The top layer, containing methanol, acid, and water, was separated. Conversely, the bottom layer (pre-treated oil) was withdrawn and washed with warm distilled water at 50 °C to remove residual sulfuric acid. Washing was repeated until the wash water reached a neutral pH. The oil was then dried in an oven set to 105 °C, and its weight was recorded at 10-minute intervals. The oil was considered dry when the weight remained constant. The FFA value of the oil was confirmed to be less than 2 mg KOH/mg (1 wt%). The yield of low-FFA oil was calculated, and the oil was characterized by proximate and instrumental analyses.

2.5. Oil Characterization

2.5.1 Physicochemical characterization

The physicochemical properties of the extracted orange seed oil were analyzed using standard test methods presented in Table 1. In contrast, the proximate composition of the seeds and the extracted oil was determined following the official methods of the Association of Official Analytical Chemists (AOAC, 2019). A Fourier transform infrared (FTIR) spectrometer and gas chromatography-mass spectrometry (GC-MS) were used to determine the functional groups and fatty acid profile, respectively.

Table 1: Standard Test Methods for Characterization of Extracted Oils

Oil property	Test methods
Moisture Contents	AOCS CA 2C-25 (2017b)
Specific gravity (S.G)	AOAC 920.212 (2000c)
Refractive index	ASTM D7483-21 (2021a)
Dynamic and kinematic viscosity	AOCS CC7-25 (2009b)
Melting point	ASTM DS5440 (2017a)
Pour point	ASTM D97 (2019c)

2.5.2 Instrumental analysis

2.5.2 .1 GC-MS analysis

GC-MS analysis was used to determine the fatty acid profile of orange seed oil samples, following AOAC 969.33 and .22 (2000d) standards. The analysis employed a Thermo Finnigan Trace GC/Trace DSQ IA1300 (E. 1 Quadrupole) with an SGE-BPX5 MS fused silica capillary column (0.25 µm) for detection, using an electron ionization system at 70 eV. Helium at 10 mL/min was the carrier gas. The injector and transfer line were set to 220 °C and 290 °C, respectively. The oven temperature was programmed to rise at 3 °C/min from 50 °C to 150 °C, hold for 10 min, then increase to 250 °C at 10 °C/min. Diluted samples (1/100, vv, in methylene chloride) of 1.00 µL were manually injected in slitless mode. Components were identified by comparing retention times with authentic standards on an SGE-BPXS capillary column, matching mass spectral peaks with authentic samples or libraries (Wiley 7N and TRLIB), and referencing published data. Then, the molecular weight of the triglyceride in the oils (Mwo) was calculated from the fatty acid profile obtained by gas chromatography analysis, using Equation (3.1)

$$Mw = 3 \times Mav + 38.049. \quad (2)$$

Where Mw = molecular weight of a triglyceride, Mav = average molecular weight of the oil, 3 = number of fatty acid chains in a triglyceride, 38.049 = molecular mass of glycerol in the triglyceride (the glycerol backbone).

2.5.2.2 FTIR Spectroscopy

The FT-IR spectra of orange seed oil samples were obtained using a SHIMADZU FT-IR-8400 instrument with a 45° ZnSe HATR crystal, a DTGS detector, and KBr as the beam splitter. The device was operated with Omnic software (Version 6.0, Thermo Nicolet). To prevent contamination and ensure accuracy, the sample holder was cleaned with acetone and dried with tissue paper. During each measurement, oil samples were directly applied to the HATR surface at a stable room temperature of 20°C, covering the mid-IR range from 650 to 4000 cm^{-1}. Forty scans were averaged at a resolution of 4 cm^{-1}. Each spectrum was recorded in triplicate and averaged. Peak fitting and smoothing were performed using OPUS 2000 software on the Shimadzu 8400S within the range 4000-650 cm^{-1}.

3.0 Result and Discussion

3.1 Oil Yield and Appearance

The Soxhlet extraction of sweet orange seed oil with n- hexane yielded an oil content of 41. 64 w %. This extraction efficiency is significant and notably higher than the 34. 00 w % yield reported by Ezekoye et al. (2019), the 37% yield reported by Sadiq (2016), and the 40 w % yield reported by Ibrahim et al. (2019). The yield falls within the range of 38. 7 wt % to 45. 8 wt % reported for Jatropha curcas seeds (Jonas et al., 2020). Orange seed is classified as an oil- bearing seed because any seed yielding up to 30 w % oil is considered suitable for industrial use (Eryilmaz et al., 2016; Koubaa et al., 2016). Researchers highlight that high oil yields from citrus seeds are crucial for transforming them from environmental waste into valuable industrial feedstock (Agu et al., 2024; Seyyedi-Mansour et al., 2024; Suri et al., 2021). This yield is comparable to those reported for some common biodiesel feedstocks and other non- edible oils, such as neem seed (42. 63%) (Genene, 2024) and jatropha seed (48. 16%) (Subroto et al., 2015). The Soxhlet method, which uses n- hexane as the solvent, is a common and effective technique for extracting oil (AOAC, 2019; Kumar et al., 2025; Mustapha et al., 2024; Ogwuche et al., 2026; Shakya et al., 2025) because n- hexane dissolves lipids well and is easy to recover (El Marji et al., 2026; Kukkohovi, 2020 ; Osuji et al., 2025). The oil' s light- yellow color indicates it has not degraded or absorbed impurities, which is favorable for subsequent steps (Palanisamy, Gevert, 2016). The moisture content of 0. 249% is not sufficiently low to be acceptable. Dehydration of the oil is essential because excess moisture can lead to triglyceride and FFA breakdown, reducing catalyst activity, biolubricant quality, and biodiesel yield during transesterification (Farouk et al., 2024; Norjannah et al., 2016 Salaheldeen et al., 2021). The measured parameters- cloud point of 12. 0 ° C, melting point of 3. 3.5 ° C, and an ester value of 62. 019%, indicating high unsaturation- show that the oil remains liquid at room temperature (28 ± 2 ° C) (Nadjamoeddin et al., 2025; Umeh & Okonkwo, .2025).

3.2 Physicochemical Properties

Table 2: Physicochemical Properties of Orange Seed Oil vs. ASTM/Industry Standards

Property	Characterized Value	Unit	ASTM/Standard Method	Standard Limit (Biodiesel/Biolubricant)
Kinematic Viscosity (@ 40°C)	29.450	mm^2/s	ASTM D445	1.9 – 6.0 (Biodiesel) / 20–50 (Light Lubricant)
Acid Value	9.24	mgKOH/g	ASTM D664	< 0.5 (Biodiesel) / < 2.0 (Lubricant)
Free Fatty Acid (FFA)	4.67	mgKOH/g	—	< 1% (for direct base-catalysis)
Specific Gravity (@ 15°C)	0.920	—	ASTM D1298	0.86 – 0.90 (Biodiesel)
Flash Point	217	°C	ASTM D93	130 min (Biodiesel) / > 200 (Lubricant)
Iodine Value	107.78	$gI_2/100g$	ASTM D1510	< 120 (Standard for stability)
Saponification Value	193.45	mgKOH/g	ASTM D5558	180 – 265 (Typical for seed oils)
Peroxide Value	0.410	meq/kg	ASTM D3584	< 10 (Freshness limit)
Cloud Point	12.00	°C	ASTM D2500	Location-dependent (Report only)

Moisture Content	0.249	%	ASTM D2709	< 0.05% (Biodiesel)
Refractive Index	1.4637	—	ASTM D1218	1.44 – 1.48 (Typical)

Kinematic viscosity is a key property of vegetable oils used as feedstocks for biodiesel and biolubricants because it directly impacts engine performance, fuel atomization, and lubrication. The kinematic viscosity of SOSO at 40°C was measured at 29.450 mm²/s. This value is notably lower than the 46.57 mm²/s earlier reported by Onyinye and Tagbo (2023), but higher than the 1.9 to 6.0 mm²/s range typical for biodiesel (ASTM D6751). However, it aligns with the 29.22 mm²/s reported for cottonseed oil by Ezidinma et al. (2015). Ayetor et al. (2015) reported that the kinematic viscosity of coconut oil decreased from 27 to 2.4 mm²/s after transesterification. Nevertheless, biodiesel made from this oil would have lower viscosity, which fits within the specified ranges, because larger fatty acid molecules are broken down into smaller methyl esters (El Marji et al., 2026; Kukkohovi, 2020; Osuji et al., 2025).

The refractive index indicates the oil's quality and purity. SOSO's refractive index of 1.437 at 30°C falls within 1.44–1.48 specified by ASTM D6751, and closely matches the 1.4626 reported for SOSO by Agu, et al., (2024) and the 1.4658 reported by Onyinye and Tagbo (2023) for sweet orange seed oil used in bio-lubricant synthesis.

The acid value and free fatty acid (FFA) content are key properties in biodiesel production. The acid value of sweet orange seed oil (9.24 mgKOH/g), which corresponds to an FFA content of 4.27 mgKOH/g, exceeds the 2 mgKOH/g limit specified by ASTM for direct alkaline catalyzed transesterification. Feedstocks with FFA levels above 1-2% (about 2-4 mgKOH/g) are unsuitable for direct alkaline transesterification because they cause soap formation, emulsions, saponification, reduced ester yield, and catalyst damage (Farouk, et al., 2024; Olatundun et al., 2024; Salaheldeen et al., 2021). Despite this high FFA content, SOSO can still be used for alkaline transesterification by first going through an acid-catalyzed esterification step (section 2.4.2) to reduce FFA levels to below 1.0 mgKOH/g before continuing with alkaline transesterification. This approach helps maximize biodiesel and biolubricant yields and quality (Olatundun et al., 2024; Salaheldeen et al., 2021). This two-step method is often used for oils with high FFA levels (Farouk, et al., 2024; Olatundun et al., 2024; Salaheldeen et al., 2021).

The measured iodine value of 107.78 meq/100g aligns with the ASTM standard (<120 meq/100g) and indicates that SOSO's fatty acid profile has a medium to high level of unsaturation. This value is significantly higher than the 31.47 meq/100g reported by Agu et al. (2024) for SOSO and also exceeds the 56.4047 meq/100g reported for SOSO by Sadiq (2016). The elevated iodine value is reflected in the 67.1% linoleic acid shown by GC-MS analysis. A higher iodine value signifies more double bonds, which can affect properties such as cloud point, pour point, and oxidative stability (Amran & Ruslan, 2022; Kumar et al., 2024; Miyuranga et al., 2022; Pradana et al., 2024). Generally, high unsaturation enhances the low-temperature performance of biodiesel and biolubricants.

The measured cloud point of 12.0°C is similar to the 11°C and 10.2°C reported for SOSO by Agu et al. (2024) and Sadiq (2016), respectively. The cloud point of 12.0°C and the melting point of 3.5°C suggest that biodiesel derived from SOSO would flow well in cold weather and potentially outperform oils with higher saturation, such as palm oil (Hazrat et al., 2020; Leng & Zhou, 2020; Yadav & Chaudhary, 2020; Yusof et al., 2021). However, higher unsaturation also makes the biodiesel more susceptible to oxidation during storage, which can lead to gum formation and engine deposits (Agregán et al., 2017; Çamur & Al-Ani, 2022; Zhang et al., 2021). Research indicates that antioxidants may be required as additives to boost oxidative stability (Agregán et al., 2017; Çamur & Al-Ani, 2022; Chizoo et al., 2023; Hazrat et al., 2021; Zhang et al., 2021).

The saponification value is another key property of triglyceride oils, reflecting the average length of fatty acid chains. A saponification value of 243.446 mgKOH/g falls within the ASTM D6751 standard range of 180 to 265 mgKOH/g for seed oils. Generally, a higher saponification value indicates shorter fatty acid chains, which reduces viscosity and improves combustion in biodiesel and biolubricants (Alsaadi & Ahmad, 2025; Neupane, 2022; Folayan et al., 2019; Giakoumis & Sarakatsanis, 2018).

The specific gravity of 0.920 is typical of vegetable oils and close to the 0.86–0.90 range specified for biodiesel (ASTM D6751). With a molecular weight of 1114.68 g/mol and a flash point of 217°C—exceeding safety standards for handling and storage—the oil is considered safe for use. Its flash point ensures suitability for high-temperature applications and surpasses safety requirements for biodiesel and lubricants.

The peroxide value of 0.410 meq/g, far lower than the <10 meq/g ASTM standard, indicates low initial oxidation, signaling good quality and stability (Agregán et al., 2017; Çamur & Al-Ani, 2022; Zhang et al., 2021). This is desirable for industrial feedstock, as higher peroxide values could increase the risk of polymerization during heating and negatively impact catalyst performance and the final product quality (Kim et al., 2018; Meng et al., 2023; Monirul et al., 2015).

3.3 Fatty Acid Profile Analysis (GC-MS)

The GC-MS chromatogram (Fig. 1) revealed several distinct peaks corresponding to the Fatty Acid groups present in the SOSO, while the major identified components are summarized in Table 3.

The GC-MS analysis of the extracted oil (Figure 1) and Table 3 shows that the oil mainly consists of unsaturated fatty acids (UFA), with Linoleic Acid (67.01%) and Oleic Acid (4.34%) making up around 71.35% of the total composition.

The most abundant component is 9,12-Octadecadienoic acid (Z,Z)-, also known as linoleic acid (C18:2), which accounts for 67.01% of the total area percentage. Next is cis-13-Octadecenoic acid (oleic acid, C18:1) at 4.34%. The saturated fatty acid (SFA) fraction, which makes up 31.13% of the total, is mainly composed of n-hexadecanoic acid (palmitic acid, C16:0) at 25.28% and octadecanoic acid (stearic acid, C18:0) at 5.75%.




Figure 1: Total Ion Chromatogram of Orange Seed Oil.

Table 3: Fatty acid Profile of sweet orange seed oil

Fatty Acid	Common Name	Total Area%	Primary Retention Times (RT)
9,12-Octadecadienoic acid (Z,Z)-	Linoleic Acid	67.01%	19.701, 20.538, 20.096
n-Hexadecanoic acid	Palmitic Acid	25.28%	16.319, 16.519, 15.973
Octadecanoic acid	Stearic Acid	5.75%	20.889
cis-13-Octadecenoic acid	Oleic Acid	4.34%	20.721
Tetradecanoic acid	Myristic Acid	0.10%	12.895

The GC-MS analysis of SOSO in the current study is shown in Table 3, while Table 4 compares GC-MS analysis results of sweet orange seed oils from the current study, seeds collected from the University of Nigeria Nsukka (Ezekoye, et al., 2019), and seeds collected from Fitidi in Oyo State, Nigeria (Nwozo, et al., 2021). These results reveal a significant disparity among them, suggesting that both the fatty acid composition and concentrations vary depending on the seed source location (Özcan et al., 2023). Additionally, small amounts of tetradecanoic acid (myristic acid) were detected at 0.10%. The ratio of unsaturated to saturated fatty acids, 2.29 to 1, indicates that biodiesel produced from this oil will flow well at low temperatures, which is important for its use as a renewable energy source.

Table 4. Comparative analysis with research implications

Fatty Acid	SOSO (Current Study) (%)	Literature (Orange Seed Oil)	
		Nwozo[a]	**Ezekoye[b]**
Linoleic Acid (C18:2	67.01	37.644	----------
Palmitic Acid (C16:0)	25.28	28.051	1.63
Stearic Acid (C18:0)	5.75	5.839	39.42
Oleic Acid (C18:1)	4.34		17.65
Isopropyl linolate	----------	12.699	---------
pentadecanoic acid	----------	9.652	---------
Butyl Linolate	----------	2.867	---------
Lauric acid	----------	---------	7.73
Palmitic acid	----------	---------	1,63
Myristic acid	0.10	---------	33.56

Source: Nwozo, et al., (2021)[a]; Ezekoye, et al., (2019)[b]

Palmitic acid (C16:0) is the main saturated component, providing a good balance of fluidity and oxidative stability (Jadhav et al., 2022; Redondo-Cuevas et al., 2018). As Jadhav et al. (2022) and the National Academies of Sciences, Engineering, and Medicine (2021) have noted, a high linoleic acid content is especially beneficial for the paint and coatings industry because it helps oils dry by linking them together. Additionally, the high level of unsaturation indicates that products made from SOSO would perform well at low temperatures, which is important for biolubricants used in temperate climates (Narayana Sarma and Vinu, 2022; Opia et al., 2023). The increased unsaturation level in triglyceride oils suggests these products will work effectively at low temperatures, which is critical for biolubricants in temperate regions.

3.4 FTIR spectrum of the orange seed oil

Figure 1 displays the FTIR spectrum of SOSO, offering key information about its molecular-level chemical structure. Triacylglycerols (TAGs), the primary components of vegetable oils, show characteristic absorption bands that dominate most of the spectrum. The Carbonyl Region (1740–1745 cm^{-1}): A sharp, intense peak around 1740 cm-1 results from the C=O stretching vibration of the ester carbonyl group in triglyceride molecules. Its high intensity and narrow width indicate many esters are present, which are necessary for converting into biodiesel (Fatty Acid Methyl Esters) or biolubricant base oils (Atadashi et al., 2013). The Aliphatic Hydrocarbon Region (3000–2800 cm^{-1}): The strong bands at 2922 cm-1 and 2853 cm^{-1} are due to the asymmetric and symmetric stretching of aliphatic CH_2 groups. This confirms the presence of long-chain fatty acids, which are essential for

biolubricants to form a strong lubricating film and for fuel applications to achieve high energy density (Bhuiya et al., 2016).




Figure 2: FT-IR spectrum of the orange seed oil

The FTIR spectrum of the Sweet Orange Seed Oil (SOSO) (Figure 2) was examined to identify the functional groups and structural markers that determine its industrial applications. The complete list of peak assignments is shown in Table 5.

Table 5: FTIR absorbance spectra and functional groups of SOSO

Wavenumber (cm−1)	Functional Group	Type of Vibration	Technical Interpretation
3472.0 – 3444.1	O-H	Stretching	Indicates low moisture and trace hydroperoxides.
3009.8	=C-H (cis)	Stretching	Confirms unsaturation; validates 67.01% Linoleic acid.
2920.4	-CH_2	Asymmetric Stretching	Methylene groups of long aliphatic hydrocarbon chains.
2853.3	-CH_2	Symmetric Stretching	Methylene groups of long aliphatic hydrocarbon chains.
2174.9 – 2150.7	C ≡ C (Alkynes)	Stretching	Presence of internal triple bonds/terminal alkyne residues.
1742.5	C=O (Ester)	Stretching	Primary carbonyl group of triglycerides.
1709.0	C=O (Acid)	Stretching	Free fatty acid (FFA) carbonyl; correlates with acid value.
1459.3	-CH_2	Bending (Scissoring)	Aliphatic chain deformation in long-chain fatty acids.
1414.5	-CH_2	Bending (Rocking)	Vibration of methylene groups adjacent to carbonyl/alkene sites.
1377.3	C-H (CH_3)	Symmetric Bending	Methyl group "umbrella" mode.
1280.3	C-O	Stretching	Functional group characteristic of ester linkages.
1239.3	C-O	Stretching	Asymmetric stretching of the triglyceride ester structure.
1161.1	C-O-C	Stretching	Primary ester bond vibration in glycerides.

1097.7	C-O	Stretching	Stretching associated with the ester/glycerol backbone.
941.2	=C-H	Out-of-plane Bending	Indicators of unsaturated fatty acid configurations.
721.2	$(CH_2)_n$	Rocking	Confirms a long hydrocarbon skeleton ($n \geq 4$).

Analysis of the spectrum revealed the presence of esters (C=O), alkenes (C=C), alkynes (C≡C), and alkanes (C–H), as well as carbonyl (C=O) and alcohol (OH) functional groups in the oil. The detection of esters (C=O), alkenes (C=C), alkynes (C≡C), and alkanes (C–H), along with carbonyl (C=O) and alcohol (OH) groups, confirms that the oil is a complex mixture of triacylglycerols with specific indicators of chemical stability and composition (Chen, et al., 2025; Chijioke, et al., 2024; Ufoma, 2023). A notable feature of the spectrum is the dual-peak structure in the carbonyl region. The intense absorption at 1742.5 cm-1 is attributed to the C=O stretching of ester groups in triglycerides, while the peak at 1709.0 cm-1 specifically indicates the C=O stretching of free fatty acids (FFAs) (Agbike, 2023; Gunarathne, et al., 2022; Mekonnen, 2023). This spectroscopic evidence correlates with the high acid value (9.24 mgKOH/g) of the oil (Khairuddin, et al., 2024; Rohman, & Indrayanto, 2023; Uçar, et al., 2024), indicating partial hydrolysis of triglycerides into free acidic components (Cocero, et al., 2024; Menalla, et al., 2024; Vicentini-Polette, et al., 2021).

The peak at 3009.8 cm-1 corresponds to the =C-H stretching of cis-olefinic double bonds. The presence of this peak confirms the high degree of unsaturation (Bathini, et al., 2018; Debabhuti, et al., 2022; Fu, et al., 2021), specifically, the 67.01% Linoleic acid content—identified by GC-MS. The aliphatic nature of this feedstock is verified by the dominant asymmetric and symmetric C-H stretching bands at 2920.4 cm^{-1} and 2853.3 cm^{-1}, which represent the methylene backbones of the fatty acid chains (Gadhiya, 2026; Li, et al., 2025; Soodoo et al., 2023; Srivastava & Mishra, 2026).

Another notable feature in the mid-infrared region is the low-intensity absorption detected between 2174.9 and 2150.7 cm^{-1}. This band is attributed to the C ≡ C stretching vibration, indicating the presence of alkyne functional groups within the lipid matrix (Bakthavatsalam, et al.,2021; Pielesz, et al., 2023; Romei, et al., 2022). Although this feature is less common than alkenes in vegetable oils, these triple-bond residues can occur in specialized non-edible seeds and suggest a unique chemical signature for the oil (Nigerian sweet orange variety) (Adeoye, et al., 2023; Magaji, et al., 2025; Ivchenko and Nifant'ev, 2025), potentially affecting the oil's reactivity during industrial processes such as polymerization or alkyd resin synthesis (Hadzich, et al., 2023; Ifijen, et al., 2022; Zohuriaan-Mehr, and Omidian, 2020). The presence of these alkynes complements the significant unsaturation identified at 3009.8 cm^{-1} (cis-alkene stretching), which also offers spectroscopic confirmation for the 67.01% Linoleic acid detected via GC-MS.

The high transmittance and lack of significant depth in the 3444.1 cm^{-1} region suggest a low concentration of O-H groups associated with moisture or primary oxidation products (Xi, et al., 2021; Zhang, et al., 2024). This confirms that the n-hexane Soxhlet extraction successfully recovered a high-purity oil while maintaining its oxidative integrity. The long-chain nature of the fatty acids (more than four carbon atoms) is further verified by the CH_2 rocking vibration at 721.2 cm^{-1}.

These spectroscopic assignments offered a thorough and consistent chemical profile, aligning the instrumental data with the reported physicochemical results. Additionally, the detailed mapping of C-O and C-H bending modes at 1161.1 cm^{-1} and 1459.3 cm^{-1} confirms the high concentration of stable triglycerides needed for high-yield biodiesel production (Lamb, 2024; Salaheldeen, et al., 2021; Verma, et al., 2024), while the presence of specific bending modes (e.g., -CH2 at 1414.5 cm^{-1}) suggests reactive sites near carbonyl groups, which are essential for the successful synthesis of alkyd resins (Arauz-Solís, et al., 2025; Hadzich, et al., 2023; Ifijen, et al., 2022). The free acid components (C-O), indicated by the 1280.3 cm^{-1} peak, demonstrate that this study provides a non-destructive method to monitor oil degradation and hydrolysis, a crucial requirement for international standards like ASTM D6751.

3.5 **The Industrial "Waste-to-Wealth" Potential of SOSO.**

Orange seeds are highly valuable in industrial applications because of their significant oil content, low acidity, and abundance of healthy fats. Using this seed oil in industry can help fruit-processing businesses to reduce waste disposal costs and create extra income by selling the seed or seed oil to producers of biofuels, cosmetics, and chemicals. This strategy aligns with the views of researchers like Tahulela, et al., (2026), who believe that transforming waste into useful products is a smart way to promote industrial growth in Africa. This method offers an effective way to reduce waste and boost economic development.

4.0. Conclusion

This study analyzed Sweet Orange Seed Oil (SOSO) extracted from Citrus sinensis residues to evaluate its potential as a sustainable industrial raw material. The research was driven by the idea that agro-industrial waste, which causes environmental problems in Nigerian landfills, has a unique chemical structure suitable for high-value industrial applications.

The key findings indicate that Soxhlet extraction with n-hexane yields a high-purity oil with a distinctive fatty acid profile, primarily composed of Linoleic acid (67.01%) and Palmitic acid (25.28%). Analytical techniques such as GC-MS and FTIR confirmed a high concentration of unsaturated fatty acids and identified stable triglyceride ester bonds, which are important for oxidative stability and flow properties. Additionally, the physicochemical properties of the extracted SOSO meet ASTM D6751 standards, confirming its suitability for producing biodiesel, biolubricants, and alkyd resins.

These results are significant for the circular bio-economy, offering a data-driven way to turn "waste" into industrial "wealth" and reduce the environmental impact of citrus processing leftovers, showing that SOSO as a viable non-edible feedstock addresses the "food vs. fuel" dilemma and promotes national industrial independence.

5.0 Recommendation

Future research should focus on the catalytic transesterification of this Nigerian SOSO variety using waste-derived heterogeneous catalysts to improve process sustainability. Additionally, exploring computational modeling tools like Artificial Neural Networks (ANN) and Artificial Neuro-Fuzzy Inference System (ANFIS) can help optimize reaction parameters for industrial-scale applications.

Private investors in the fruit-processing industry should consider setting up integrated oil-recovery units that combine seed collection and processing.

We need to conduct more research on how to extend OSO's lifespan by preventing its oxidation when exposed to air. This would make it suitable for use in premium cosmetics or medicines.

The government in Nigeria should provide special tax incentives to companies that utilize waste-to-wealth technologies, particularly those that use local, non-edible materials like orange seeds. This can help decrease the country's dependence on imported synthetic oils. By doing so, the government can motivate more businesses to adopt these innovative technologies and generate new opportunities for growth and development. It is a simple yet effective way to promote sustainability and bolster the local economy.

To support environmental conservation, local farming officials in Nigeria and other citrus-growing regions should promote small juice producers to adopt methods that prevent waste. This can help lessen the environmental damage caused by discarding seeds and other waste openly. By utilizing all parts of the fruit, these small businesses can reduce their ecological footprint and increase the sustainability of their operationsR

Acknowledgements

The authors acknowledge the Project Development Agency (PRODA) Enugu, Nigeria for their assistance with the laboratory work. This research did not receive any form of financial assistance from any source

Nomenclature

FFA= Free Fatty Acid, mgKOH/g;

KOH= Potassium Hydroxide;

SOSO = Sweet Orange Seed Oil;

Y = Oil yield, %;;

Declaration of Generative AI and AI-assisted technologies in the writing process

During the preparation of this work the author(s) used Grammarly in order to correct grammatical errors. After using this tool/service, the author(s) reviewed and edited the content as needed and take(s) full responsibility for the content of the publication.

References

Adeoye, A.O., Quadri, R.O. and Lawal, O.S., 2023. Biomass waste pyrolysis in the context of Nigeria's oil and gas industry: an overview, *International Journal of Ambient Energy*, 44(1), pp. 2507-2523. doi: 10.1080/01430750.2023.2256325.

Agbike, J.E., 2023. *Application of Infrared Spectroscopy in Probing the Effects of Fatty Acid Molecules on Prostate Cancer Cells*. Doctoral dissertation. The University of Manchester (United Kingdom).

Agregán, R., Lorenzo, J.M., Munekata, P.E., Dominguez, R., Carballo, J. and Franco, D., 2017. Assessment of the antioxidant activity of Bifurcaria bifurcata aqueous extract on canola oil. Effect of extract concentration on the oxidation stability and volatile compound generation during oil storage, *Food Research International*, 99, pp. 1095-1102. doi: 10.1016/j.foodres.2016.10.029.

Al-Okbi, S.Y., Mohammad, A.A., Azab, D.E.S.H. and Mohammed, S.E., 2025. Valorization of orange seeds oil as a health-promoting ingredient in functional mayonnaise production, *Journal of Food Measurement and Characterization*, pp. 1-12. doi: 10.1007/s11694-025-03870-x.

Alsaadi, S., Shakir, M.A. and Ahmad, M.I., 2025. A comparative review of vegetative and animal-based biodiesel: feedstock selection, synthesis method, characterization technique, and economic perspective, *Journal of Climate Change*, 11(2), p. 22. doi: 10.70917/jcc-2025-013.

Amran, N.A., Bello, U. and Ruslan, M.S.H., 2022. The role of antioxidants in improving biodiesel's oxidative stability, poor cold flow properties, and the effects of the duo on engine performance: A review, *Heliyon*, 8(7). doi: 10.1016/j.heliyon.2022.e09846.

AOAC., 2019. *Official Methods of Analysis of AOAC International*. 21st edn. Gaithersburg, MD, USA: AOAC International.

AOAC International., 2000. Standard test method for iodine value of edible oils (AOAC 920.159), doi: 10.1093/9780197610923.001.0001.

AOAC International., 2000. Standard test method for saponification number of oils and fats (AOAC 920.160), doi: 10.1093/9780197610923.001.0001.

AOAC International., 2000. Standard test method for specific gravity of oils (AOAC 920.212), doi: 10.1093/9780197610923.001.0001.

AOAC International., 2019. *Official Methods of Analysis of AOAC International*. 21st edn. Gaithersburg, MD, USA: AOAC International. doi: 10.1093/9780197610923.001.0001.

AOCS., 1989 Preparation of methyl esters of fatty acids (AOCS Ca 5a-40), doi: 10.1002/9780470025113.a0513.

AOCS., 1996. Peroxide value of fats and oils (AOCS Cd 8-53), doi: 10.1002/9780470025113.a0512.

AOCS., 2009a. Acid value of fats and oils (AOCS Cd 3d-63), doi: 10.1002/9780470025113.a0510.

AOCS., 2009b. Refractive index of fats and oils (AOCS Cc 7-25), doi: 10.1002/9780470025113.a0511.

AOCS., 2017 Moisture and volatile matter by hot plate method (AOCS Ca 2c-25), doi: 10.1002/9780470025113.a0509.

Arauz-Solís, A.B., Avalos-Belmontes, F., Martínez-Cartagena, M.E., Banda-Villanueva, A., Torres-Lubian, J.R. and Ventura-Hunter, C., 2025 Recent advances in hyperbranched alkyd resins, *Journal of Coatings Technology and Research*, 22(1), pp. 149-169. doi: 10.1007/s11998-024-00995-4.

ASTM D6751., no date. *Standard Specification for Biodiesel Fuel Blend Stock (B100) for Middle Distillate Fuels*. ASTM International.

ASTM International., 2017 Standard test method for determining the melting point of fats and oils (ASTM D5440-17), doi: 10.1520/D5440-17.

ASTM International., 2019a. Standard test method for heat of combustion of liquid hydrocarbon fuels by bomb calorimeter (ASTM D240-19), doi: 10.1520/D0240-19.

ASTM International., 2019b. Standard test method for pour point of petroleum products (ASTM D97-19), doi: 10.1520/D0097-19.

ASTM International (2021a) *Standard test method for determination of dynamic viscosity and derived kinematic viscosity of liquids by oscillating piston viscometer (ASTM D7483-21)*. doi: 10.1520/D7483-21129834.

ASTM International., 2021b. Standard test method for refractive index and refractive dispersion of hydrocarbon liquids (ASTM D1218-21), doi: 10.1520/D1218-21.

ASTM International., 2022. Standard test method for water and sediment in middle distillate fuels by centrifuge (ASTM D2709-22), doi: 10.1520/D2709-22.

ASTM International., 2023. Standard test method for density, relative density, or API gravity of crude petroleum and liquid petroleum products by hydrometer method (ASTM D1298-23), doi: 10.1520/D1298-23.

ASTM International., 2024a. *Standard specification for biodiesel fuel blend stock (B100) for middle distillate fuels (ASTM D6751-24)*. West Conshohocken, PA: ASTM International. doi: 10.1520/D6751-24.

ASTM International., 2024b Standard test method for acid number of petroleum products by potentiometric titration (ASTM D664-24), doi: 10.1520/D0664-24.

ASTM International., 2024c. Standard test method for cloud point of petroleum products and liquid fuels (ASTM D2500-24), doi: 10.1520/D2500-24.

ASTM International., 2024d. Standard test method for flash point by Pensky-Martens closed cup tester (ASTM D93-24), doi: 10.1520/D0093-24.

ASTM International., 2024e. Standard test method for kinematic viscosity of transparent and opaque liquids (ASTM D445-24), doi: 10.1520/D0445-24.

ASTM International., 2024f. Standard test method for saponification number of petroleum products (ASTM D94-24), doi: 10.1520/D0094-24.

Attia, N.K., El-Mekkawi, S.A., Elardy, O.A. and Abdelkader, E.A., 2020. Chemical and rheological assessment of produced biolubricants from different vegetable oils, *Fuel*, 271, pp. 117578. doi: 10.1016/j.fuel.2020.117578.

Ayetor, G.K., Sunnu, A. and Parbey, J., 2015. Effect of biodiesel production parameters on viscosity and yield of methyl esters: Jatropha curcas, Elaeis guineensis and Cocos nucifera, *Alexandria Engineering Journal*, 54(4), pp. 1285-1290. doi: 10.1016/j.aej.2015.09.011.

Bakthavatsalam, S., Dodo, K. and Sodeoka, M., 2021. A decade of alkyne-tag Raman imaging (ATRI): applications in biological systems', *RSC Chemical Biology*, 2(5), pp. 1415-1429. doi: 10.1039/D1CB00116G.

Bathini, V., Kalakandan, S.K., Pakkirisamy, M. and Ravichandran, K., 2018. Structural elucidation of peanut, sunflower and gingelly oils by using FTIR and 1H NMR spectroscopy', *Pharmacognosy Journal*, 10(4), pp. 753-757. doi: 10.5530/pj.2018.4.126.

Bhuiya, M., Rasul, M., Khan, M., Ashwath, N. and Azad, A., 2016. Prospects of 2nd generation biodiesel as a sustainable fuel—Part: 1 selection of feedstocks, oil extraction techniques and conversion technologies, *Renewable and Sustainable Energy Reviews*, 55, pp. 1109-1128. doi: 10.1016/j.rser.2015.04.163.

Çamur, H. and Al-Ani, A.M.R. 2022. Prediction of oxidation stability of biodiesel derived from waste and refined vegetable oils by statistical approaches, *Energies*, 15(2), p. 407. doi: 10.3390/en15020407.

Chen, M., Zhang, T., Zhang, J., Liu, C., Chen, D. and Zhang, J., 2025. Unveiling the Micro-Mechanism of Functional Group Regulation for Enhanced Dielectric Properties in Novel Natural Ester Insulating Oil TME-C10, *Molecules*, 30(7), p. 1431. doi: 10.3390/molecules30071431.

Chijioke, S.C., Onuoha, C.H. and Chukwudoruo, C.S., 2024. 'Bioactive compositions and identification of functional groups of selected medicinal plants', *GSC Biological and Pharmaceutical Sciences*, 27(1), pp. 008-027. doi: 10.30574/gscbps.2024.27.1.0106.

Chizoo, E., Okechukwu, M.F., Dominic, O.O., Kingsley, A.A., Chimamkpam, A.S., Mariagorretti, M.C. and Chinonso, E.P., 2023. Renewable diesel synthesis from sesame indicum (bene) seed oil using novel heterogeneous biocatalyst derived from the Chrysophyllum albidium seed coat, *Heliyon*, 9(11). doi: 10.1016/j.heliyon.2023.e22006.

Cocero, M.J., Menalla, E., Garcia-Serna, J. and Cantero, D.A., 2024. Hydrothermal Hydrolysis of Triglycerides: Tunable and Intensified Production of Diglycerides, Monoglycerides, and Fatty Acids, doi: 10.2139/ssrn.4768481.

Debabhuti, N., Mukherjee, S., Neogi, S., Sharma, P., Sk, U.H., Maiti, S. and Bandyopadhyay, R., 2022. A study of vegetable oil modified QCM sensor to detect β-pinene in Indian cardamom, *Talanta*, 236, p. 122837. doi: 10.1016/j.talanta.2021.122837.

Dubey, P., Tripathi, G., Mir, S.S. and Yousuf, O., 2023. Current scenario and global perspectives of citrus fruit waste as a valuable resource for the development of food packaging film, *Trends in Food Science & Technology*, 141, p. 104190. doi: 10.1016/j.tifs.2023.104190.

El Marji, L., Sharara, M., El Chakik, D., Nakad, M., Assaf, J.C. and Estephane, J., 2026. A Comparative Review of Biomass Conversion to Biodiesel with a Focus on Sunflower Oil: Production Pathways, Sustainability, and Challenges, *Processes*, 14(3), p. 441. doi: 10.3390/pr14030441.

Eryilmaz, T., Yesilyurt, M.K., Cesur, C. and Gokdogan, O., 2016. Biodiesel production potential from oil seeds in Turkey, *Renewable and Sustainable Energy Reviews*, 58, pp. 842-851. doi: 10.1016/j.rser.2015.12.172.

Ezekoye, V., Adinde, R., Ezekoye, D. and Ofomatah, A., 2019. Syntheses and characterization of biodiesel from citrus sinensis seed oil, *Scientific African*, 6, e00217. doi: 10.1016/j.sciaf.2019.e00217.

Ezidinma Timothy. A Onukwuli D.O, Uzoh C.F., 2015. 'Synthesis and Characterization of Water- Reducible Alkyd Resin from Cottonseed Oil, *International Journal of Engineering and Applied Sciences*, 2(12), pp. 2394-3661.

Fadairo, A., Adeyemi, G., Egenhoff, S., Obia, S., Oni, O., Oladepo, A. and Nwaokwu, R., 2023 Improving the flowability of waxy crude oil using orange seed oil derived additive, in *SPE Nigeria Annual International Conference and Exhibition*. SPE, p. D031S021R006. doi: 10.2118/217254-MS.

Farag, M.A., Eid, S.M. and El-Shamy, S., 2025. Gas chromatography-mass spectrometry and Fourier-transform infrared spectroscopy coupled to chemometrics for metabolome analysis of different milk types in the light of green analytical chemistry, *PeerJ*, 13, e19921. doi: 10.7717/peerj.19921.

Farouk, S.M., Tayeb, A.M., Abdel-Hamid, S.M. and Osman, R.M., 2024. Recent advances in transesterification for sustainable biodiesel production, challenges, and prospects: a comprehensive review, *Environmental Science and Pollution Research*, 31(9), pp. 12722-12747. doi: 10.1007/s11356-024-32027-4.

Folayan, A.J., Anawe, P.A.L., Aladejare, A.E. and Ayeni, A.O., 2019. Experimental investigation of the effect of fatty acids configuration, chain length, branching and degree of unsaturation on biodiesel fuel properties obtained from lauric oils, high-oleic and high-linoleic vegetable oil biomass, *Energy Reports*, 5, pp. 793-806. doi: 10.1016/j.egyr.2019.06.013.

Fu, X., Su, J., Hou, L., Zhu, P., Hou, Y., Zhang, K. and Xu, J. 2021. Physicochemical and thermal characteristics of Moringa oleifera seed oil, *Advanced Composites and Hybrid Materials*, 4(3), pp. 685-695. doi: 10.1007/s42114-021-00302-4.

Gadhiya, C.N., Prajapati, V. and Z. Dholakiya, B., 2026. Sustainable Niger Seed Oil-Derived Polyurethane Coatings for Wood Protection: Development, Characterization, and Performance Analysis, *Journal of Macromolecular Science, Part B*, pp. 1-26. doi: 10.1080/00222348.2026.2613102.

Genene, D., 2024.Extraction of Oil from Azadirachta indica and Moringa stenopetala Seeds and Evaluation of its Physicochemical Properties', *MANAS Journal of Engineering*, 12(1), pp. 163–176. doi: 10.51354/mjen.1377816.

Giakoumis, E.G. and Sarakatsanis, C.K., 2018. Estimation of biodiesel cetane number, density, kinematic viscosity and heating values from its fatty acid weight composition, *Fuel*, 222, pp. 574-585. doi: 10.1016/j.fuel.2018.02.187.

Gunarathne, R., Marikkar, N., Mendis, E., Yalegama, C., Jayasinghe, L. and Ulpathakumbura, S., 2022. Mid-IR spectral characterization and chemometric evaluation of different solvent extracts of coconut testa flour, *Journal of Food Chemistry and Nanotechnology*, 8(3), pp. 69-75.

Hadzich, A., Flores, S., Masucci, A.E., Gomez, E.D. and Groß, G.A., 2023. NMR and GPC analysis of alkyd resins: influence of synthesis method, vegetable oil and polyol content, *Polymers*, 15(9), p. 1993. doi: 10.3390/polym15091993.

Hazrat, M.A., Rasul, M.G., Khan, M.M.K., Mofijur, M., Ahmed, S.F., Ong, H.C. and Show, P.L., 2021. Techniques to improve the stability of biodiesel: a review, *Environmental Chemistry Letters*, 19(3), pp. 2209-2236. doi: 10.1007/s10311-020-01166-8.

Ifijen, I.H., Maliki, M., Odiachi, I.J., Aghedo, O.N. and Ohiocheoya, E.B., 2022 Review on solvents based alkyd resins and water borne alkyd resins: impacts of modification on their coating properties, *Chemistry Africa*, 5(2), pp. 211-225. doi: 10.1007/s42250-022-00318-3.

Ivchenko, P.V. and Nifant'ev, I.E. 2025. The chemistry of oleates and related compounds in the 2020s, *Green Chemistry*, 27(1), pp. 41-95. doi: 10.1039/D4GC04862H.

Jadhav, H.B., Gogate, P.R., Waghmare, J.T. and Annapure, U.S., 2022. Comparative assessment of thermo-oxidative stability of palm oil designer lipid and palm oil blends as frying medium, *Applied Food Research*, 2(1), p. 100039. doi: 10.1016/j.afres.2021.100039.

Jonas, M., Ketlogetswe, C. and Gandure, J., 2020. Variation of Jatropha curcas seed oil content and fatty acid composition with fruit maturity stage, *Heliyon*, 6(1). doi: 10.1016/j.heliyon.2020.e03285.

Kamińska, W., Grygier, A., Rzyska-Szczupak, K., Przybylska-Balcerek, A., Stuper-Szablewska, K. and Neunert, G., 2025. Nutritional Quality, Fatty Acids Profile, and Phytochemical Composition of Unconventional Vegetable Oils, *Molecules*, 30(15), p. 3269. doi: 10.3390/molecules30153269.

Khairuddin, M.M., Abdullah, A. and Nor, N.M., 2024. Physicochemical Properties, Fatty Acids Composition and Characterization of Helianthus annuus seed oIl, *Malaysian Journal of Analytical Sciences*, 28(6), pp. 1258-1269.

Khalighi, S., 2024. *Biodiesel production: determination of thermodynamic properties and monitoring of the transesterification reaction*. Doctoral dissertation. Universidade de Coimbra (Portugal).

Kim, J.K., Jeon, C.H., Lee, H.W., Park, Y.K., Min, K.I., Hwang, I.H. and Kim, Y.M., 2018. Effect of accelerated high temperature on oxidation and polymerization of biodiesel from vegetable oils, *Energies*, 11(12), p. 3514. doi: 10.3390/en11123514.

Koubaa, M., Mhemdi, H., Barba, F.J., Roohinejad, S., Greiner, R. and Vorobiev, E., 2016. Oilseed treatment using ultrasound and microwave to improve oil yield and quality: An overview, *Food Research International*, 85, pp. 59-66. doi: 10.1016/j.foodres.2016.04.007.

Kudli, L.P., 2023 *Sustainability evaluation of azelaic acid from techno-economic analysis and environmental life cycle assessment of sustainable azelaic acid production*. Doctoral dissertation. University of Illinois at Urbana-Champaign.

Kukkohovi, M., 2020. *Catalyst-free simultaneous esterification and transesterification of low-quality fats and oils to FAME under subcritical water conditions and their purification*.

Kumar, S., Rai, A. and Prasad, K., 2025. Enhancing sustainability and quality: A comparative study of sunflower seed oil extraction methods and physico-chemical characterization, *Sustainable Chemistry One World*, 6, p. 100060. doi: 10.1016/j.scowo.2025.100060.

Kumar, S., Singhal, M.K. and Sharma, M.P. 2024. Improvement of oxidation stability and cold flow properties of biodiesel using mixed oil strategy, *Waste and Biomass Valorization*, 15(2), pp. 649-664. doi: 10.1016/j.scowo.2025.100060.

Lamb, A., 2024. *Experimental and modelling studies of heterogeneous catalysts for biodiesel production*. Doctoral dissertation. RMIT University.

Laverdura, U.P., Rossi, L., Ferella, F., Courson, C., Zarli, A., Alhajyoussef, R. and Gallucci, K., 2020. Selective catalytic hydrogenation of vegetable oils on lindlar catalyst, *ACS omega*, 5(36), pp. 22901-22913. doi: 10.1021/acsomega.0c02280.

Leng, L., Li, W., Li, H., Jiang, S. and Zhou, W., 2020. 'Cold flow properties of biodiesel and the improvement methods: a review, *Energy & Fuels*, 34(9), pp. 10364-10383. doi: 10.1021/acs.energyfuels.0c01912.

Li, J., Li, Z., Yan, Y., Shao, D., Guo, Y. and Lin, R., 2025. Study on the structure-property relationship of starch/PLA composite films modified by the synergistic effect of aromatic rings and aliphatic chains, *Polymer Degradation and Stability*, p. 111567. doi: 10.1016/j.polymdegradstab.2025.111567.

Lucia, C., Laudicina, V.A., Badalucco, L., Galati, A., Palazzolo, E., Torregrossa, M. and Corsino, S.F., 2022. Challenges and opportunities for citrus wastewater management and valorisation: A review, *Journal of Environmental Management*, 321, p. 115924. doi: 10.1016/j.jenvman.2022.115924.

Magaji, M.B., Elinge, C.M., Birnin-Yauri, A.U. and Umar, S., 2025. Production and Characterization of Acid-Base Biofunctional Catalyst from Desert Date (Balanite aegyptiaca) Seed Shells (DDSS) for Biodiesel Production, *Bulletins of Natural and Applied Sciences*, 2(1), pp. 11-20.

Maqbool, Z., Khalid, W., Atiq, H.T., Koraqi, H., Javaid, Z., Alhag, S.K. and Al-Farga, A.. 2023 Citrus waste as source of bioactive compounds: Extraction and utilization in health and food industry, *Molecules*, 28(4), p. 1636. doi: 10.3390/molecules28041636.

Mekonnen, K.D., 2023. Fourier transform infrared spectroscopy as a tool for identifying the unique characteristic bands of lipid in oilseed components: Confirmed via Ethiopian indigenous desert date fruit, *Heliyon*, 9(4). doi: 10.1016/j.heliyon.2023.e14699.

Menalla, E., Serna, J.G., Cantero, D. and Cocero, M.J., 2024. Hydrothermal hydrolysis of triglycerides: Tunable and intensified production of diglycerides, monoglycerides, and fatty acids, *Chemical Engineering Journal*, 493, p. 152391. doi: 10.1016/j.cej.2024.152391.

Meng, J., Xu, W., Meng, F., Wang, B., Zhao, P., Wang, Z. and Yang, Y., 2023. Effects of waste cooking oil biodiesel addition on combustion, regulated and unregulated emission characteristics of common-rail diesel engine, *Process Safety and Environmental Protection*, 178, pp. 1094-1106. doi: 10.1016/j.psep.2023.08.065.

Miyuranga, K.V., Arachchige, U.S., Jayasinghe, R.A. and Samarakoon, G., 2022. Purification of residual glycerol from biodiesel production as a value-added raw material for glycerolysis of free fatty acids in waste cooking oil, *Energies*, 15(23), p. 8856. doi: 10.3390/en15238856.

Monirul, I.M., Masjuki, H.H., Kalam, M.A., Zulkifli, N.W.M., Rashedul, H.K., Rashed, M.M. and Mosarof, M.H., 2015 A comprehensive review on biodiesel cold flow properties and oxidation stability along with their improvement processes, *RSC advances*, 5(105), pp. 86631-86655. doi: 10.1039/C5RA09555G.

Moreno-Gómez, A.L., Gutiérrez-Antonio, C., Gómez-Castro, F.I. and Hernández, S., 2020. Production of biojet fuel from waste raw materials: A review, *Process systems engineering for biofuels development*, pp. 149-171. doi: 10.1002/9781119582694.ch6.

Mruthunjaya, K., Manjula, S.N., Sharma, H., Anand, A. and Kenchegowda, M., 2025. Valorization of Citrus Waste for the Synthesis of Value Added Products, in *Valorization of Citrus Food Waste*. Cham: Springer Nature Switzerland, pp. 179-213. doi: 10.1007/978-3-031-77999-2_7.

Mustapha, S., Habib, M.U., Ma'aruf, A.M., Mustapha, A., Shehu, H., Madaniyyu, S.Y. and Inuwa, M.I., 2024. Sustainable Technique for Neem (Azadirachta Indica) Seed Oil Extraction: Optimization and Characterization, *African Journal of Environment and Natural Science Research*, 7(2), pp. 218-228. doi: 10.52589/AJENSR-5H1FVLHR.

Narayana Sarma, R. and Vinu, R., 2022. Current status and future prospects of biolubricants: properties and applications, *Lubricants*, 10(4), p. 70. doi: 10.3390/lubricants10040070.

National Academies of Sciences, Engineering, and Medicine., 2021. Fat, in *Nutrient Requirements of Dairy Cattle: Eighth Revised Edition*. National Academies Press (US).

Nayak, C., Bhatlu, L.D., Chelluboyana, V.R., Sahoo, S.P., Behera, S.K., Bhaisal, T. and Elgarahy, A.M., 2025. An in-depth comparative analysis of fuel evolution: tracking physico-chemical characteristics in conventional diesel, e-diesel, biodiesel, and aged biodiesel, *Biofuels*, pp. 1-47. doi: 10.1080/17597269.2025.2578575.

Nazri, M.Z., 2025. Application of Fourier Transform Infrared (FTIR) Spectroscopy, Gas Chromatography and Chemometric Analyses for Halal Authentication in Food Products, *Journal of Academia*, 13(2), pp. 209-223. doi: 10.24191/joa.v13i2.6201.

Neupane, D., 2022. Biofuels from renewable sources, a potential option for biodiesel production, *Bioengineering*, 10(1), p. 29. doi: 10.3390/bioengineering10010029.

Nwozo, S.O., Omotayo, O.O. and Nwawuba, S.U., 2021. Nutritional evaluation of sweet orange citrus sinensis seed oil, *MOJ Ecol Environ Sci*, 6(1), pp. 15-20. doi: 10.15406/mojes.2021.06.00208.

Ogunkunle, O. and Ahmed, N.A., 2021) 'A review of non-edible vegetable oils as a potential feedstock for biodiesel production', *Energy Reports*, 7, pp. 1390-1406. doi: 10.1016/j.egyr.2021.02.045.

Ogwuche, C.E., Emwanta, D.O., Etoh, P.A., Ekoro, I., Okorhi-Damisa, F.B. and Akpevwe, O.P., 2026. Gc-ms profiling, antimicrobial, antioxidant and anti-inflammatory analysis of the n-hexane extract of the seeds of raphia hookeri obtained in delta state, *International Journal of Renewable Energy and Environment*, 4(1), pp. 1-10.

Olatundun, T.O., Popoola, V., Fakoyede, P.D., Adebayo, D.O., Kehinde, E.D., Adetoro, Q. and Anyalebechi, P.E., 2024. Production of biodiesel from palm kernel oil through base-catalyzed trans-esterification process, World J. Adv. Res. Rev, 23, pp. 2054-2081. doi: 10.30574/wjarr.2024.23.1.2093.

Onukwuli, D.O. and Uzoh, C.F., no date. Synthesis and Characterization of Water-Reducible Alkyd Resin from Cottonseed Oil, *International Journal of Engineering and Applied Sciences*, 2(12), pp. 257766.

Onyia, T., P C, A., CE, E. and Onyia, M.C., 2024. Optimization of Biodiesel Production from Palm Kernel oil Using Heterogeneous Catalyst: Physicochemical Characterization and Process Parameter Effects, doi: 10.2139/ssrn.4874580.

Onyinye, A.O. and Tagbo, N.J, 2023. Extraction and analysis of Citrus Sinensis Seed Oil (CSSO) for prospective use as bio lubricant., *UNIZIK J Eng Appl Sci*, 1(1), pp. 41-50.

Opia, A.C., Abdollah, M.F.B., Hamid, M.K.A. and Veza, I., 2023. A review on bio-lubricants as an alternative green product: tribological performance, mechanism, challenges and future opportunities, *Tribology Online*, 18(2), pp. 18-33. doi: 10.2474/trol.18.18.

Osuji, I.D., Akomah, U.C., Oyefeso, I.E., Ibekwere, V.C., Ezejelue, B.R., Obiagwu, C.C. and Ekeodu, O.E., 2025. Sustainable Biodiesel Production from Sawdust Oil Using Snail Shell-Derived Bio-Catalyst, *African Journal of Environmental Sciences and Renewable Energy*, 20(1), pp. 195-216. doi: 10.62154/ajesre.2025.020.01022.

Özcan, M.M., Öztürk, Ö. and Lemiasheuski, V. (2023) 'Quality properties, fatty acid composition, and mineral contents of some citrus seeds and oils extracted by solvent extraction', *Erwerbs-obstbau*, 65(1), pp. 127-132. doi: 10.1007/s10341-022-00675-w.

Palanisamy, S. and Gevert, B.S., 2016. Study of non-catalytic thermal decomposition of triglyceride at hydroprocessing condition, *Applied Thermal Engineering*, 107, pp. 301-310. doi: 10.1016/j.applthermaleng.2016.06.167.

Pandit, C., Banerjee, S., Pandit, S., Lahiri, D., Kumar, V., Chaubey, K.K. and Joshi, S.J., 2023. Recent advances and challenges in the utilization of nanomaterials in transesterification for biodiesel production, *Heliyon*, 9(4). doi: 10.1016/j.heliyon.2023.e15475.

Patel, N., Kumar, R. and Vishwakarma, D.K., 2019. Status and prospect of precision farming in India, in *Agricultural Impacts of Climate Change [Volume 1]*. CRC Press, pp. 119-159. doi: 10.1201/9780429326349-8.

Pielesz, A., Biniaś, D., Waksmańska, W. and Bobiński, R., 2023. Lipid bands of approx. 1740 cm− 1 as spectral biomarkers and image of tissue oxidative stress, *Spectrochimica Acta Part A: Molecular and Biomolecular Spectroscopy*, 286, p. 121926. doi: 10.1016/j.saa.2022.121926.

Pradana, Y.S., Makertihartha, I.G.B., Indarto, A., Prakoso, T. and Soerawidjaja, T.H., 2024 A review of biodiesel cold flow properties and its improvement methods: towards sustainable biodiesel application, *Energies*, 17(18), pp. 4543. doi: 10.3390/en17184543.

Pratiksha and Adhikary, M., 2024. Industrial production of citrus by-products and its processing techniques, in *Citrus Fruits and Juice: Processing and Quality Profiling*. Singapore: Springer Nature Singapore, pp. 391-417. doi: 10.1007/978-981-99-8699-6_16.

Redondo-Cuevas, L., Castellano, G., Torrens, F. and Raikos, V., 2018. Revealing the relationship between vegetable oil composition and oxidative stability: A multifactorial approach, *Journal of Food Composition and Analysis*, 66, pp. 221-229. doi: 10.1016/j.jfca.2017.12.027.

Reyna-Ávila, E.D., Luna-Maldonado, A.I., Rodríguez-Fuentes, H., Sinagawa-García, S.R., Gómez-Leyva, J.F. and Arredondo-Valdez, J. (2025) 'Response of Spinacia oleracea varieties cultivated in a plant factory with artificial lighting', *Journal of Applied Horticulture*, 27(4), pp. 560-566.

Ribeiro, D.C., Ramalho, A., Serra, A.C. and Coelho, J., 2025. Biolubricants Based on Epoxidized Vegetable Oils: A Review on Chemical Modifications, Tribological Properties, and Sustainability, *Lubricants*, 13(12), p. 510. doi: 10.3390/lubricants13120510.

Rohman, A. and Indrayanto, G., 2023. Fourier transform infrared spectroscopy combined with multivariate analysis for quality analysis of fats and oils, in *Food quality analysis*. Academic Press, pp. 49-70. doi: 10.1016/B978-0-323-95988-9.00007-2.

Romei, M.G., von Krusenstiern, E.V., Ridings, S.T., King, R.N., Fortier, J.C., McKeon, C.A. and Londergan, C.H., 2022. Frequency changes in terminal alkynes provide strong, sensitive, and solvatochromic Raman probes of biochemical environments, *The Journal of Physical Chemistry B*, 127(1), pp. 85-94. doi: 10.1021/acs.jpcb.2c06176.

Sadiq, A.S., 2016. Assessment of Nigeria sweet orange seed oil for biodiesel production, *catalyst*, 2(1), p. 2.

Salaheldeen, M., Mariod, A.A., Aroua, M.K., Rahman, S.A., Soudagar, M.E.M. and Fattah, I.R., 2021. Current state and perspectives on transesterification of triglycerides for biodiesel production', *Catalysts*, 11(9), p. 1121. doi: 10.3390/catal11091121.

Shakya, A.K., Jindal, N. and Riar, C.S., 2025. A comprehensive review of conventional, green, and assisted techniques for chia (Salvia hispanica L.) oil extraction, *Food Production, Processing and Nutrition*, 7(1), p. 67. doi: 10.1186/s43014-025-00346-9.

Singh, A., Monica and Rajpoot, S., 2025. Promoting the Global Economies by Sustainable Use and Management of Agricultural Waste, in *Innovative Technologies for Waste Management: Strategies, Challenges and Future Directions*. Cham: Springer Nature Switzerland, pp. 209-246. doi: 10.1007/978-3-031-97184-6_10.

Sirohi, R., Tarafdar, A., de Souza Vandenberghe, L.P., Taherzadeh, M.J. and Pandey, A., (eds) 2025. *Sustainable Technologies for Food Waste Management*. CRC Press. doi: 10.1201/9781032706030.

Soodoo, N., Bouzidi, L. and Narine, S.S., 2023. Fundamental structure-function relationships in vegetable oil-based lubricants: a critical review, *Lubricants*, 11(7), p. 284. doi: 10.3390/lubricants11070284.

Srivastava, S. and Mishra, A., 2026. A Novel Eri (Philosamia ricini)-Flaxseed (Linum usitatissimum) Oil Blend: Advanced Analytical Characterization by GC-MS and FTIR Spectroscopy Coupled with Multivariate Analysis and In Vitro Antimicrobial Assays, *Food Analytical Methods*, 19(3), p. 121. doi: 10.1007/s12161-026-03044-5.

Subroto, E., Manurung, R., Heeres, H.J. and Broekhuis, A.A., 2015. Optimization of mechanical oil extraction from Jatropha curcas L. kernel using response surface method, *Industrial Crops and Products*, 63, pp. 294–302. doi: 10.1016/j.indcrop.2014.08.050.

Syahir, A., Zulkifli, N., Masjuki, H., Kalam, M., Alabdulkarem, A., Gulzar, M., Khuong, L. and Harith, M., 2017. A review on bio-based lubricants and their applications, *Journal of Cleaner Production*, 168, pp. 997-1016. doi: 10.1016/j.jclepro.2017.09.106.

Tahulela, A.C., Sharma, Y. and Suri, A., 2026. Climate-Compatible Agricultural Waste Management Strategies for Resilient Land Use in South Africa: A Systematic Review of Circular Innovations, *The BRICS Imperative: Confronting Climate Challen*. doi: 10.1007/978-3-032-05932-1_1.

Uçar, B., Gholami, Z., Svobodová, K., Hradecká, I. and Hönig, V., 2024, A comprehensive study for determination of free fatty acids in selected biological materials: a review, *Foods*, 13(12), p. 1891. doi: 10.3390/foods13121891.

Ufoma, o.M., 2023. *Extraction, characterization and thermal stability studies with tigernut oil*.

Verma, C. and Dubey, S., (eds) 2024. *Biomass Wastes for Sustainable Industrial Applications: A Waste-to-Wealth Approach*. CRC Press. doi: 10.1201/9781003466833.

Verma, S., Sahu, D. and Almutairi, B.O., 2024. Production and characterization of biodiesel fuel produced from third-generation feedstock, *Frontiers in Materials*, 11, p. 1454120. doi: 10.3389/fmats.2024.1454120.

Vicentini-Polette, C.M., Ramos, P.R., Gonçalves, C.B. and De Oliveira, A.L., 2021. Determination of free fatty acids in crude vegetable oil samples obtained by high-pressure processes, *Food Chemistry: X*, 12, p. 100166. doi: 10.1016/j.fochx.2021.100166.

Warra, A.A. and Prasad, M.N., 2024. *Industrial Crops: Bioresources to Biotechnology*. CRC Press. doi: 10.1201/9780429346279.

Xi, Z., Li, X. and Xi, K., 2021. Study on the reactivity of oxygen-containing functional groups in coal with and without adsorbed water in low-temperature oxidation, *Fuel*, 304, p. 121454. doi: 10.1016/j.fuel.2021.121454.

Yadav, K., Kumar, N. and Chaudhary, R., 2020. A review on cold flow properties of biodiesel and their improvement, in *IOP Conference Series: Materials Science and Engineering*. IOP Publishing, 804(1), p. 012027. doi: 10.1088/1757-899X/804/1/012027.

Yusof, S.N.A., Sidik, N.A.C., Asako, Y., Basharie, S.M. and Mohamed, S.B., 2021. Characterization of crude palm oil (CPO), corn oil and waste cooking oil for biodiesel production, J. Adv. Res. Fluid Mech. Therm. Sci., 86, pp. 136-46. doi: 10.37934/arfmts.86.2.136146.

Zhang, L., Wen, C., Li, S. and Yang, M., 2024. Evolution and oxidation properties of the functional groups of coals after water immersion and air drying, *Energy*, 288, p. 129709. doi: 10.1016/j.energy.2023.129709.

Zhang, N., Li, Y., Wen, S., Sun, Y., Chen, J., Gao, Y. and Yu, X. 2021. Analytical methods for determining the peroxide value of edible oils: A mini-review, *Food chemistry*, 358, AOAC International.

Zohuriaan-Mehr, M.J. and Omidian, H., 2020. Petroleum resins: an overview, *Journal of Macromolecular Science, Part C: Polymer Reviews*, 40(1), pp. 23-49. doi: 10.1081/MC-100100577.